



INTERLOCKED EXHAUST HOSE

Interlocked Exhaust Hose Cross Section



Description

Our exhaust hoses are produced in a wide range of 10 sizes, metals and weights. This range is available to provide the right hose for the application at the most economical cost. Interlocked exhaust hose utilizes a fully interlocked construction for strength and durability while allowing the hose to have excellent flexing characteristics. The normal configuration of exhaust hose is unpacked and fully extended. In order to minimize leakage, however, exhaust hose can be supplied packed upon request.

End Fittings

Standard pipe couplings, nipples and fixed or floating flanges can be attached to exhaust hose. Any special type of fitting can be adapted to fit this hose. Attachment can be by welding, brazing or with adhesives. Additionally, hose clamps and automotive muffler clamps can be used.

Specifications

Our exhaust hoses are produced in galvanized steel and stainless steel as standard but are also available in aluminum and bronze as specials. The strip thickness and thus the hose weight can be selected to match the application depending upon the degree of rough handling and the abrasive conditions of the service. We make three different weights of exhaust hose as indicated in the following tables.

| Series | Weight Designation | Strip Thickness |
|--------|--------------------|-----------------|
| IE30 | Light | .010" to .012" |
| IE50 | Standard Heavy | .018" to .020" |

The size range of exhaust hose is from 1/2" to 8" inside diameter. For sizes larger than 8"10, use the standard conveyor hose (up to 20"10).

Applications

Some typical uses of exhaust hose are: engine exhaust and vacuum and collection service, conveying, ventilating lines, and protective casing for cable and tubing.

| | | |
|------|--|----------------|
| IE65 | | .024" to .026" |
|------|--|----------------|